



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle (Chrome / EagleBrite®) Dolly Truck, model _____ . Constructed of four wire shelves with patented QuadTruss® design (patent #5,390,803), aluminum truck dolly with wraparound bumper, four numbered posts, and 5" casters. Shipped knocked down.



Options / Accessories

- Ledges
- Dividers
- Shelf markers

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065
www.eaglegrp.com
www.eaglegrpnews.com
www.eaglemhc.com

For custom configuration or fabrication needs, contact our **SpecFAB® Division**.
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.:	_____
Project No.:	_____
S.I.S. No.:	_____

Dolly Trucks

MODELS:

- | | | |
|-----------------------------------|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> DT1836-* | <input type="checkbox"/> DT2136-* | <input type="checkbox"/> DT2436-* |
| <input type="checkbox"/> DT1848-* | <input type="checkbox"/> DT2148-* | <input type="checkbox"/> DT2448-* |
| <input type="checkbox"/> DT1860-* | <input type="checkbox"/> DT2160-* | <input type="checkbox"/> DT2460-* |

* See chart on back for complete model numbers.

Design and Construction Features

- Four shelves with patented QuadTruss® design (patent #5,390,803), making shelves up to 25% stronger and provides a retaining ledge for increased storage stability and product retention.
- Four posts numbered on vertical one-inch increments to help ensure fast and level assembly — shelving can be adjusted up and down every inch for optimum cart configuration.
- Open wire construction promotes higher visibility by allowing light to pass through the shelves, permits greater air circulation which helps reduce dust and contamination build up, and increases the effectiveness of fire suppression systems.
- Fast assembly without tools. Numerically calibrated grooved posts, tapered high-temperature-resistant plastic split sleeves and shelf collars combine to make shelving assembly a simple two-step exercise:
 - 1) Snap the split sleeves onto the posts at the location of your choice;
 - 2) Slide the collars of the shelf over the split sleeves.
 A positive lock between the shelf and the split sleeves is created without the use of any tools, becoming stronger as additional weight is added to the shelving.
- Aluminum truck dolly with wraparound bumper.
- Four designated 5" x 1 1/4" (127 x 32mm) casters.
- Overall height is 69" (1753mm).
- Shipped knocked-down.

Certifications / Approvals



AutoQuotes



EG01.08 Rev. 05/23

Spec sheets available for viewing, printing or downloading from our online literature library at our websites

Eagle Foodservice Equipment, Eagle MHC, and SpecFAB® are divisions of Eagle Group. ©2023 by the Eagle Group



Profit from the Eagle Advantage®

 Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Dolly Trucks

with Eaglebrite® shelf unit model #	with chrome shelf unit model #	shelf dimensions				dolly dimensions				weight lbs. kg	caster type	wheel tread
		width		length		width		length				
		in.	mm	in.	mm	in.	mm	in.	mm			
DT1836-ZS	DT1836-CS	18"	457	36"	914	23 ³ / ₄ "	603	40 ¹ / ₈ "	1038	72 32.7	swivel	resilient
DT1836-ZSP	DT1836-CSP	18"	457	36"	914	23 ³ / ₄ "	603	40 ¹ / ₈ "	1038	72 32.7	swivel	poly
DT1836-ZSB	DT1836-CSB	18"	457	36"	914	23 ³ / ₄ "	603	40 ¹ / ₈ "	1038	72 32.7	swivel/brake	resilient
DT1836-ZSBP	DT1836-CSBP	18"	457	36"	914	23 ³ / ₄ "	603	40 ¹ / ₈ "	1038	72 32.7	swivel/brake	poly
DT1848-ZS	DT1848-CS	18"	457	48"	1219	23 ³ / ₄ "	603	52 ¹ / ₈ "	1343	86 39.0	swivel	resilient
DT1848-ZSP	DT1848-CSP	18"	457	48"	1219	23 ³ / ₄ "	603	52 ¹ / ₈ "	1343	86 39.0	swivel	poly
DT1848-ZSB	DT1848-CSB	18"	457	48"	1219	23 ³ / ₄ "	603	52 ¹ / ₈ "	1343	86 39.0	swivel/brake	resilient
DT1848-ZSBP	DT1848-CSBP	18"	457	48"	1219	23 ³ / ₄ "	603	52 ¹ / ₈ "	1343	86 39.0	swivel/brake	poly
DT1860-ZS	DT1860-CS	18"	457	60"	1524	23 ³ / ₄ "	603	64 ¹ / ₈ "	1648	100 45.4	swivel	resilient
DT1860-ZSP	DT1860-CSP	18"	457	60"	1524	23 ³ / ₄ "	603	64 ¹ / ₈ "	1648	100 45.4	swivel	poly
DT1860-ZSB	DT1860-CSB	18"	457	60"	1524	23 ³ / ₄ "	603	64 ¹ / ₈ "	1648	100 45.4	swivel/brake	resilient
DT1860-ZSBP	DT1860-CSBP	18"	457	60"	1524	23 ³ / ₄ "	603	64 ¹ / ₈ "	1648	100 45.4	swivel/brake	poly
DT2136-ZS	DT2136-CS	21"	533	36"	914	26 ¹ / ₄ "	680	40 ¹ / ₈ "	1038	82 37.2	swivel	resilient
DT2136-ZSP	DT2136-CSP	21"	533	36"	914	26 ¹ / ₄ "	680	40 ¹ / ₈ "	1038	82 37.2	swivel	poly
DT2136-ZSB	DT2136-CSB	21"	533	36"	914	26 ¹ / ₄ "	680	40 ¹ / ₈ "	1038	82 37.2	swivel/brake	resilient
DT2136-ZSBP	DT2136-CSBP	21"	533	36"	914	26 ¹ / ₄ "	680	40 ¹ / ₈ "	1038	82 37.2	swivel/brake	poly
DT2148-ZS	DT2148-CS	21"	533	48"	1219	26 ¹ / ₄ "	680	52 ¹ / ₈ "	1343	98 44.5	swivel	resilient
DT2148-ZSP	DT2148-CSP	21"	533	48"	1219	26 ¹ / ₄ "	680	52 ¹ / ₈ "	1343	98 44.5	swivel	poly
DT2148-ZSB	DT2148-CSB	21"	533	48"	1219	26 ¹ / ₄ "	680	52 ¹ / ₈ "	1343	98 44.5	swivel/brake	resilient
DT2148-ZSBP	DT2148-CSBP	21"	533	48"	1219	26 ¹ / ₄ "	680	52 ¹ / ₈ "	1343	98 44.5	swivel/brake	poly
DT2160-ZS	DT2160-CS	21"	533	60"	1524	26 ¹ / ₄ "	680	64 ¹ / ₈ "	1648	114 51.7	swivel	resilient
DT2160-ZSP	DT2160-CSP	21"	533	60"	1524	26 ¹ / ₄ "	680	64 ¹ / ₈ "	1648	114 51.7	swivel	poly
DT2160-ZSB	DT2160-CSB	21"	533	60"	1524	26 ¹ / ₄ "	680	64 ¹ / ₈ "	1648	114 51.7	swivel/brake	resilient
DT2160-ZSBP	DT2160-CSBP	21"	533	60"	1524	26 ¹ / ₄ "	680	64 ¹ / ₈ "	1648	114 51.7	swivel/brake	poly
DT2436-ZS	DT2436-CS	24"	610	36"	914	29 ³ / ₄ "	756	40 ¹ / ₈ "	1038	90 40.8	swivel	resilient
DT2436-ZSP	DT2436-CSP	24"	610	36"	914	29 ³ / ₄ "	756	40 ¹ / ₈ "	1038	90 40.8	swivel	poly
DT2436-ZSB	DT2436-CSB	24"	610	36"	914	29 ³ / ₄ "	756	40 ¹ / ₈ "	1038	90 40.8	swivel/brake	resilient
DT2436-ZSBP	DT2436-CSBP	24"	610	36"	914	29 ³ / ₄ "	756	40 ¹ / ₈ "	1038	90 40.8	swivel/brake	poly
DT2448-ZS	DT2448-CS	24"	610	48"	1219	29 ³ / ₄ "	756	52 ¹ / ₈ "	1343	112 50.8	swivel	resilient
DT2448-ZSP	DT2448-CSP	24"	610	48"	1219	29 ³ / ₄ "	756	52 ¹ / ₈ "	1343	112 50.8	swivel	poly
DT2448-ZSB	DT2448-CSB	24"	610	48"	1219	29 ³ / ₄ "	756	52 ¹ / ₈ "	1343	112 50.8	swivel/brake	resilient
DT2448-ZSBP	DT2448-CSBP	24"	610	48"	1219	29 ³ / ₄ "	756	52 ¹ / ₈ "	1343	112 50.8	swivel/brake	poly
DT2460-ZS	DT2460-CS	24"	610	60"	1524	29 ³ / ₄ "	756	64 ¹ / ₈ "	1648	134 60.8	swivel	resilient
DT2460-ZSP	DT2460-CSP	24"	610	60"	1524	29 ³ / ₄ "	756	64 ¹ / ₈ "	1648	134 60.8	swivel	poly
DT2460-ZSB	DT2460-CSB	24"	610	60"	1524	29 ³ / ₄ "	756	64 ¹ / ₈ "	1648	134 60.8	swivel/brake	resilient
DT2460-ZSBP	DT2460-CSBP	24"	610	60"	1524	29 ³ / ₄ "	756	64 ¹ / ₈ "	1648	134 60.8	swivel/brake	poly

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglegrpnews.com • www.eaglehmc.com

Printed in U.S.A.

©2023 by Eagle Group

Rev. 05/23

Spec sheets available for viewing, printing or downloading from our online literature library at our websites

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.