



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Director's Choice® Hot/Cold Unit, model _____.
Type 304 stainless steel construction. 16 gauge stainless steel 2"-tall top. Dual temperature hot or cold operation. Pre-wired with hot/cold selector switch, required thermostatic controls and pilot light. Welded 1½" square tubular stainless steel base. 5" poly tread swivel casters—two with brake. Predrilled to accommodate accessories.



hot/cold unit with optional tray slide and end panels

Options / Accessories

- Laminated end panels
- Stainless steel end panels
- Stainless steel front panel
- Stainless steel tray slide*
- Work shelf**
- Rear doors and panels***
- Sneeze guards - single tier
- Sneeze guards - double tier
- Display lights for overshelf
- Removable stainless undershelf
- Specify laminate _____
- Custom options (see EG8154)

* Available in solid ribbed, square tubular or round tubular. For front, rear, or ends.

** Available in hardwood, stainless steel, poly, or Richlite®. For front, rear, or ends.

*** Available in hinged, solid, or louvered

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our SpecFAB® Division.

Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____


Director's Choice® Hot/Cold Units

MODELS:

- DCS2-HCFU-A
- DCS3-HCFU-A
- DCS4-HCFU-B
- DCS4-HCFU-C
- DCS5-HCFU-B
- DCS5-HCFU-C
- DCS6-HCFU-B
- DCS6-HCFU-C

Design and Construction Features

- Dual temperature hot or cold operation.
- Fiberglass insulation on all sides.
- Stainless steel inner liner with coved corners and 3/4" (20mm) I.P.S. drain.
- Hot Mode: Immersion-type heating element (water required), with stainless steel sheath cover.
- Cold Mode: Self-contained condensing unit with sealed compressor. Fully charged with CFC-free refrigerant.
- Thermostatic control for hot and cold service.
- Pre-wired with hot/cold selector switch, required thermostatic controls and pilot light. Provided with 6-foot long cord with twist-lock plug.
- Type 304 stainless steel construction.
- 16 gauge type 304 stainless steel top is 30" (762mm) front-to-back and 2" (51mm) tall.
- 34" (864mm) standard working height complies with ADA guidelines for accessibility standards.
- Welded 1½" (38mm) square tubular type 304 stainless steel base construction.
- Open base on three sides – 7/8" (183mm) tall type 304 stainless steel apron on operator's side.
- 5" (127mm) poly tread swivel casters (two with brake).
- Standard holly berry red front laminate panel (Wilsonart® D307-60) on heavy gauge galvanized subpanel.






Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com



Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Director's Choice® Hot/Cold Units



# of top openings	model #	electrical data		NEMA plug	length		weight	
		Hot Mode	Cold Mode		in.	mm	lbs.	kg
2	DCS2-HCFU-A	16.7A 120V 2,000W	2.4A 120V 1/5HP	L5-30P	36"	914	190	86.2
3	DCS3-HCFU-A	16.7A 120V 2,000W	2.4A 120V 1/5HP	L5-30P	50"	1270	220	99.8
4	DCS4-HCFU-B	14.4A 208V 3,000W	7.5A 120V 1/4HP	L14-30P	64"	1626	250	113.4
4	DCS4-HCFU-C	12.5A 240V 3,000W	7.5A 120V 1/4HP	L14-30P	64"	1626	250	113.4
5	DCS5-HCFU-B	19.3A 208V 4,000W	9.8A 120V 1/3HP	L14-30P	78"	1981	270	122.5
5	DCS5-HCFU-C	16.7A 240V 4,000W	9.8A 120V 1/3HP	L14-30P	78"	1981	270	122.5
6	DCS6-HCFU-B	19.3A 208V 4,000W	9.8A 120V 1/3HP	L14-30P	96"	2438	340	154.2
6	DCS6-HCFU-C	16.7A 240V 4,000W	9.8A 120V 1/3HP	L14-30P	96"	2438	340	154.2

Optional laminate end panels available. To order, add suffix "**-LEP**" to model number. Example: DSC3-HCFU-A-**LEP**
 Optional stainless steel front panel in lieu of laminate front panel available. To order, add suffix "**-S**" to model number. Example: DCS4-HCFU-B-**S**
 Optional stainless steel end panels available. To order, add suffix "**-SEP**" to model number. Example: DSC4-HCFU-C-**S-SEP**

EAGLE GROUP
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • Fax: 302-653-2065
 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440
 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.
 ©2018 by Eagle Group
 Rev. 02/18

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.