

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Panco 26 Series Pan Rack, aluminum model ______. Aluminum construction with frame and cross supports joined with two-piece die-stamped aluminum gusset, riveted to frame and cross supports. 1¼" x 1½" tray slides with raised beads to minimize friction, slides riveted to frame. Slide spacing to be 5", 3", or 2½" to accommodate 11, 18, 20, or 24 full size sheet pans. Furnished with 5"-diameter swivel casters. Unit shipped knocked down.

Eagle Panco 26 Series Pan Rack, stainless steel model ______. Stainless steel construction with 1" square tubular frame and cross supports. 1%6" x 1%6" x 1%6" stainless steel tray slide with a raised bead edge riveted to stainless steel vertical tube. Slide spacing to be 5", 3", or 2" to accommodate 11, 18, 20, or 30 full size sheet pans. Furnished with 5"-diameter casters. Unit shipped assembled.



26 Series rack

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: quotes@eaglegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

Panco® 26 Series Racks

MODELS:	
□ <i>0UR-2611-5</i>	□ OUR-2611-5-SR
□ <i>0UR-2618-3</i>	□ <i>0UR-2618-3-SR</i>
□ <i>0UR-2620-3</i>	□ 0UR-2620-3-SR
□ 0UR-2624-2	□ <i>0UR-2624-2-SR</i>

Features on Aluminum Models

- Frame and supports are 1" (25mm) square aluminum tubing with .063" wall. Each frame and cross support is joined with extruded aluminum junctions.
- Tray slides are extruded aluminum angle 1½" high x 1½" wide x 0.1" thick (32 x 41 x 3mm) bearing surface with two raised beads providing a minimum of friction. Slides are welded to vertical posts.
- Casters are 5" (127mm)-diameter NSF-approved, non-marking swivel stem plated casters with polymer tread.
- Side-to-side crossbracing.
- Shipped knocked down—factory assembly available.

Features on Stainless Steel Models

- Frame and cross supports are 1" (25mm) square heavy gauge wall stainless tubing with all-welded construction.
- Tray slides are 18 gauge stainless steel, 1% high x 1% lip (37 x 48mm) with raised bead to minimize friction, riveted to vertical uprights.
- Casters are 5" (127mm)-diameter NSF-approved, non-marking swivel stem plated casters with polymer tread.
- Front-to-back and side-to-side crossbracing.
- Shipped fully welded.

Options / Accessories

- lue Casters with locking brakes
- ☐ Rotary donut bumpers
- ☐ Perimeter bumpers*
- Vertical corner bumpers
- Pan stops

*Factory-welded assembly required for all aluminum models specified with perimeter bumpers. See catalog sheet EG60.24 for Panco® accessories.

Certifications / Approvals






EG60.01 Rev. 02/13



Item No.:	
Project No.:	
S.I.S. No.:	


Panco® 26 Series Racks

Aluminum Racks



		—- о	verall di	mensi	ons —	$\overline{}$	slid	ing				
	l wic	l width		depth		height		space		we	weight	
model #	in.	mm	in.	mm	in.	mm	in.	mm	capacity	lbs.	kg	
OUR-2611-5	28½"	724	19"	483	69"	1753	5″	127	11	37	16.8	
OUR-2618-3	28½"	724	20"	508	66%"	1686	3″	76	18	43	19.5	
OUR-2620-3	28½"	724	20"	508	72"	1829	3″	76	20	53	24.0	
OUR-2624-2	28½"	724	20"	508	66%"	1686	21/4"	57	24	56	25.4	

Stainless Steel Racks



		<u> </u>	verall dir	nensi	ons ———	¬ sl	l sliding			
	l width		dep	oth	height	l s	pace	pan	n weight	
model #	in.	mm	in.	mm	in. mr	n in.	mm	capacity	lbs.	kg
OUR-2611-5-SR	28½"	724	20"	508	66¾″ 168	6 5"	127	11	112	50.8
OUR-2618-3-SR	28½"	724	20"	508	66¾″ 168	6 3"	76	18	129	58.5
OUR-2620-3-SR	28½"	724	20"	508	72½″ 184	2 3"	76	20	158	71.6
OUR-2624-2-SR	28½"	724	20"	508	66%″ 168	6 21/4"	57	24	161	73.0

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2013 by Eagle Group

Rev. 02/13