



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Anti-Splash Floor Trough with fiberglass grating, model _____ . Unit constructed of 14/304 stainless steel all-welded construction. Patented anti-splash design (patent #D519,618 S) assures complete drainage while preventing splash back onto the floor. Drain accommodates up to a 4"-diameter pipe and comes standard with a stainless steel removable perforated basket. Fiberglass grating to be 1" high yellow polyester material with a non-slip grit surface. Tapered "I" beam construction for ease of cleaning and drainage. Gray color grating available.



*anti-splash floor trough with
fiberglass grating*

Options / Accessories

- ☐ ADA-compliant grating*

Item No.:	_____
Project No.:	_____
S.I.S. No.:	_____

Anti-Splash Floor Troughs with Subway-Style Yellow Fiberglass Grating

MODELS:

- | | | |
|--|--|--|
| ☐ ASFT-1218-FG | ☐ ASFT-1548-FG | ☐ ASFT-1884-FG |
| ☐ ASFT-1224-FG | ☐ ASFT-1560-FG | ☐ ASFT-1896-FG |
| ☐ ASFT-1230-FG | ☐ ASFT-1572-FG | ☐ ASFT-18120-FG |
| ☐ ASFT-1236-FG | ☐ ASFT-1584-FG | ☐ ASFT-2424-FG |
| ☐ ASFT-1248-FG | ☐ ASFT-1596-FG | ☐ ASFT-2430-FG |
| ☐ ASFT-1260-FG | ☐ ASFT-15120-FG | ☐ ASFT-2436-FG |
| ☐ ASFT-1272-FG | ☐ ASFT-1824-FG | ☐ ASFT-2448-FG |
| ☐ ASFT-1284-FG | ☐ ASFT-1830-FG | ☐ ASFT-2460-FG |
| ☐ ASFT-1296-FG | ☐ ASFT-1836-FG | ☐ ASFT-2472-FG |
| ☐ ASFT-12120-FG | ☐ ASFT-1848-FG | ☐ ASFT-2484-FG |
| ☐ ASFT-1524-FG | ☐ ASFT-1860-FG | ☐ ASFT-2496-FG |
| ☐ ASFT-1530-FG | ☐ ASFT-1872-FG | ☐ ASFT-24120-FG |
| ☐ ASFT-1536-FG | | |

Design and Construction Features

- Patented "anti-splash" design (patent #D519,618 S) assures complete drainage, while preventing splash back onto floor.
- 14 gauge type 304 stainless steel all-welded construction.
- Built-in pitch towards drain ensures complete drainage.
- Stainless steel drain accommodates up to a 4" (102mm) diameter pipe, and features a removable perforated stainless steel basket.
- Comes with yellow fiberglass grating. Floor troughs with gray fiberglass grating available (in place of yellow). To order, add suffix "G" to model number. Example: ASFT-1224-FGG
- Floor troughs with gray ADA-compliant grating* available. To order, add suffix "-ADA" to end of model number. Example: ASFT-1224-FG-ADA
- Custom sizes available. Consult factory for details.

* For Floor Troughs with Fiberglass Grating, optional ADA-compliant Grating is wide T-Bar fiberglass. ADA-compliant Grating is available in gray color only.

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA
Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065
www.eaglegrp.com
www.eaglehmc.com

For custom configuration or fabrication needs, contact our SpecFAB® Division.
Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Certifications / Approvals



AutoQuotes



EG25.01A Rev. 07/25

Spec sheets available for viewing, printing or downloading from our online literature library at our websites



Eagle Foodservice Equipment, Eagle MHC, and SpecFAB® are divisions of Eagle Group. ©2025 by the Eagle Group



Profit from the Eagle Advantage®

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Anti-Splash Floor Troughs with Subway-Style Yellow Fiberglass Grating



See chart below for dimensions A through E

Grating Used in Various Floor Troughs

Floor Trough (dimension D)	Floor Trough (dimension E)	Grating Used - Quantity and Length
18" (457mm)	15" (381mm)	one 15" (381mm)
24" (610mm)	21" (533mm)	one 12" (305mm) and one 9" (229mm)
30" (762mm)	27" (686mm)	three 9" (229mm)
36" (914mm)	33" (838mm)	two 12" (305mm) and one 9" (229mm)
48" (1219mm)	45" (1143mm)	three 12" (305mm) and one 9" (229mm)
60" (1524mm)	57" (1448mm)	four 12" (305mm) and one 9" (229mm)
72" (1829mm)	69" (1753mm)	five 12" (305mm) and one 9" (229mm)
84" (2134mm)	81" (2057mm)	six 12" (305mm) and one 9" (229mm)
96" (2438mm)	93" (2362mm)	seven 12" (305mm) and one 9" (229mm)
120" (3048mm)	117" (2972mm)	nine 12" (305mm) and one 9" (229mm)

12" (305mm)-WIDE TROUGHs				15" (381mm)-WIDE TROUGHs				18" (457mm)-WIDE TROUGHs				24" (610mm)-WIDE TROUGHs				dimension D		dimension E	
dimension A: 7" (178mm)				dimension A: 10" (254mm)				dimension A: 13" (330mm)				dimension A: 19" (483mm)							
dimension B: 9" (229mm)				dimension B: 12" (305mm)				dimension B: 15" (381mm)				dimension B: 21" (533mm)							
dimension C: 12" (305mm)				dimension C: 15" (381mm)				dimension C: 18" (457mm)				dimension C: 24" (610mm)							
weight				weight				weight				weight							
lbs.	kg	model #		lbs.	kg	model #		lbs.	kg	model #		lbs.	kg	model #		in.	mm	in.	mm
45	20.4	ASFT-1218-FG		n/a	n/a	n/a		n/a	n/a	n/a		n/a	n/a	n/a		18"	457	15"	381
48	21.8	ASFT-1224-FG		52	23.6	ASFT-1524-FG		83	37.7	ASFT-1824-FG		105	47.6	ASFT-2424-FG		24"	610	21"	533
57	25.9	ASFT-1230-FG		59	26.8	ASFT-1530-FG		105	47.6	ASFT-1830-FG		125	56.7	ASFT-2430-FG		30"	762	27"	686
67	30.7	ASFT-1236-FG		78	35.4	ASFT-1536-FG		126	57.2	ASFT-1836-FG		149	67.6	ASFT-2436-FG		36"	914	33"	838
112	50.8	ASFT-1248-FG		131	59.4	ASFT-1548-FG		168	76.2	ASFT-1848-FG		198	89.8	ASFT-2448-FG		48"	1219	45"	1143
123	55.8	ASFT-1260-FG		146	66.2	ASFT-1560-FG		182	82.6	ASFT-1860-FG		247	112.0	ASFT-2460-FG		60"	1524	57"	1448
130	59.0	ASFT-1272-FG		150	68.0	ASFT-1572-FG		195	88.5	ASFT-1872-FG		250	113.4	ASFT-2472-FG		72"	1829	69"	1753
138	62.6	ASFT-1284-FG		189	85.7	ASFT-1584-FG		221	100.3	ASFT-1884-FG		254	115.2	ASFT-2484-FG		84"	2134	81"	2057
150	68.0	ASFT-1296-FG		219	99.3	ASFT-1596-FG		245	111.1	ASFT-1896-FG		275	124.7	ASFT-2496-FG		96"	2438	93"	2362
209	94.8	ASFT-12120-FG		228	103.4	ASFT-15120-FG		261	118.4	ASFT-18120-FG		294	133.4	ASFT-24120-FG		120"	3048	117"	2972

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglehmc.com

Printed in U.S.A.
 ©2025 by Eagle Group

Rev. 07/25

Spec sheets available for viewing, printing or downloading from our online literature library at our websites

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.